

Allclean

Surface cleaner

► Professional quality

Features

- Universal surface cleaner
- Dissolves grease quickly
- Safe cleaning
- Evaporates very quickly
- Leaves behind no oil film
- Powerful solvent effect
- Does not attack materials

Benefits of use

- Removes tar, oil, putty, grease, silicone, adhesive, corrosion protection agents etc. quickly and safely
- Time saving
- Suitable for use on plastics, metals, glass, painted surfaces etc.
- Also for acrylic

Areas of application

- Pre-cleaning of surfaces which are bonded with beko products, e.g. **ALLCON 10**, **Tackcon**, **Allbond-Fluid** etc.
- Removes surplus unhardened PU adhesive, e.g. **ALLCON 10**, **Tackcon**, **Fibcon**, from surfaces without smearing
- For the removal of adhesive residues from protective films and labels, including on acrylic baths
- Effortlessly removes sealant residues in motor vehicles and heating/sanitation systems
- Can be used to clean cable ends (e.g. when fitting shrink sleeves)



Allclean

Surface cleaner

Content 500 ml

Art.-No. 266 120 0500EN

Content 100 ml

Art.-No. 266 120 0100EN

Other
chemical
products

Range of use

- ▶ Motor vehicle trade
- ▶ Print shops
- ▶ Paint shops
- ▶ Industrial enterprises
- ▶ Painting and decorating
- ▶ Petrol stations
- ▶ Building trade
- ▶ Wood trade

Directions for use

Put some **beko Allclean** on a soft, clean cloth. Wipe the surface to be cleaned, applying light pressure. Dry off with a soft cloth. If required, repeat the process. Check surfaces for colour fastness.

Caution

- ▶ Treat freshly painted surfaces with care.
- ▶ Test small areas before general use.
- ▶ Do not apply to leather or waxed surfaces.
- ▶ Keep out of the reach of children.
- ▶ Do not ingest or breathe in.
- ▶ Avoid contact with skin and eyes.
- ▶ Protect clothing.
- ▶ In the case of incorrect or improper application, any product warranty becomes void.
- ▶ For professional and industrial use only.
- ▶ Please observe safety data sheet.

Technical data

Basis	Dearomatised hydrocarbon			
Colour	transparent			
Smell	characteristic			
Density	approx. 0,75 g/cm ³			
Viscosity	low viscosity			
Storage life	24 months			
Storage	in well sealed containers, cool and dry			
Contents/ packaging	Can 500 ml	6 pcs/box	756 pcs/pallet	Art.-No. 266 120 0500EN
	Can 250 ml	12 pcs/box	960 pcs/pallet	Art.-No. 266 120 0250EN
	Can 100 ml	24 pcs/box	3024 pcs/pallet	Art.-No. 266 120 0100EN