

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

beko Hydro-Stop Sockelbeschichtung - pastös
Supercedes Date: 03-Nov-2022

Revision date 15-Mar-2023
Revision Number 2.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name beko Hydro-Stop Sockelbeschichtung - pastös
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

beko GmbH
Rappenfeldstr. 5
DE-86653 Monheim
Tel: +49 (0) 9091 90898-0
Fax: +49 (0) 9091 90898-29

E-mail address info@beko-group.com

1.4. Emergency telephone number

Germany Poison Control Center Mainz - 24 hour emergency service – phone: +49 (0) 6131/19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Signal word

None

Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH208 - Contains Trimethoxyvinylsilane & N-(3-(trimethoxysilyl)propyl)ethylenediamine. May produce an allergic reaction
EUH210 - Safety data sheet available on request

2.3. Other hazards

SAFETY DATA SHEET

beko Hydro-Stop Sockelbeschichtung - pastös
Supersedes Date: 03-Nov-2022

Revision date 15-Mar-2023
Revision Number 2.01

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	258-207-9	52829-07-9	0.1- <1	Eye Dam. 1 (H318) Repr. 2 (H361f) Aquatic Acute 1 (H400) Aquatic Chronic 2 (H411)	-	01-2119537297-32-XXXX
Trimethoxyvinylsilane	(014-049-00-0) 220-449-8	2768-02-7	0.1- <1	Skin Sens. 1B (H317) Acute Tox. 4 (H332) Flam. Liq. 3 (H226)	-	01-2119513215-52-XXXX
Titanium dioxide	(022-006-00-2) 236-675-5	13463-67-7	0.1- <1	[C]	-	01-2119489379-17-XXXX
N-(3-(trimethoxysilyl)propyl)ethylenediamine	217-164-6	1760-24-3	0.1- <1	Eye Dam. 1 (H318) Skin Sens. 1B (H317) STOT SE 3 (H335)	-	01-2119970215-39-XXXX
Diocetyl tin oxide	212-791-1	870-08-6	0.1 - <0.5	STOT SE 2 (H371)	-	01-2119971268-27-xxxx
Ethyl silicate	(014-005-00-0) 201-083-8	78-10-4	0.1 - <0.3	Acute Tox. 4 (H332) Eye Irrit. 2 (H319) STOT SE 3 (H335) Flam. Liq. 3 (H226)	-	01-2119496195-28-xxxx

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring

Full text of H- and EUH-phrases: see section 16

SAFETY DATA SHEET

beko Hydro-Stop Sockelbeschichtung - pastös
Supersedes Date: 03-Nov-2022

Revision date 15-Mar-2023
Revision Number 2.01

Air contaminants formed when using the substance or mixture as intended

Chemical name	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Methyl alcohol 67-56-1	(603-001-00-X) 200-659-6	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C \geq 10% STOT SE 2 :: 3% \leq C<10%	-	-	01-2119433307-44-XXXX

This product does not contain candidate substances of very high concern at a concentration \geq 0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Notes

See section 16 for more information

Chemical name	Notes
Titanium dioxide - 13463-67-7	V,W,10

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	If medical advice is needed, have product container or label at hand.
Inhalation	Remove to fresh air. If symptoms persist, call a doctor.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.
Skin contact	Wash off immediately with soap and plenty of water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Do NOT induce vomiting. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Call a doctor or poison control centre immediately. Small amounts of toxic methanol are released by hydrolysis.
Self-protection of the first aider	Wear personal protective clothing (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	None known.
-----------------	-------------

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Treat symptomatically. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.
------------------------	-------------------------------------------------------------------------------------------------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

SAFETY DATA SHEET

beko Hydro-Stop Sockelbeschichtung - pastös
Supersedes Date: 03-Nov-2022

Revision date 15-Mar-2023
Revision Number 2.01

Suitable Extinguishing Media Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Thermal decomposition can lead to release of irritating gases and vapours.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO₂).

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Wear self contained breathing apparatus for fire fighting if necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation. Use personal protective equipment as required. Do not get in eyes, on skin, or on clothing.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from food, drink and animal feedingstuffs.

Recommended storage temperature Keep at temperatures between 10 and 35 °C.

SAFETY DATA SHEET

beko Hydro-Stop Sockelbeschichtung - pastös
Supercedes Date: 03-Nov-2022

Revision date 15-Mar-2023
Revision Number 2.01

7.3. Specific end use(s)

Specific use(s)
Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Limestone 1317-65-3	-	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³
Methyl alcohol 67-56-1	TWA: 200 ppm TWA: 260 mg/m ³ *	TWA: 200 ppm TWA: 266 mg/m ³ STEL: 250 ppm STEL: 333 mg/m ³ Sk*
Titanium dioxide 13463-67-7	-	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³
Diocetyl tin oxide 870-08-6	-	TWA: 0.1 mg/m ³ STEL: 0.2 mg/m ³ Sk*
Ethyl silicate 78-10-4	TWA: 44 mg/m ³ TWA: 5 ppm	TWA: 5 ppm TWA: 44 mg/m ³ STEL: 15 ppm STEL: 132 mg/m ³

Chemical name	European Union	Ireland	United Kingdom
Methyl alcohol 67-56-1	-	15 mg/L (urine - Methanol end of shift)	-

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Long term Systemic health effects	Inhalation	2.82 mg/m ³	
worker Long term Systemic health effects	Dermal	1.6 mg/kg	

Trimethoxyvinylsilane (2768-02-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Inhalation	27,6 mg/m ³	

SAFETY DATA SHEET

beko Hydro-Stop Sockelbeschichtung - pastös
Supersedes Date: 03-Nov-2022

Revision date 15-Mar-2023
Revision Number 2.01

worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d	
------------------------------------------------	--------	----------------	--

Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m ³	

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Inhalation	35.5 mg/m ³	
Long term Systemic health effects worker	Dermal	5 mg/kg bw/d	
Short term Systemic health effects worker	Dermal	5 mg/kg bw/d	

Diocetyl tin oxide (870-08-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	0.05 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	0.004 mg/m ³	

Ethyl silicate (78-10-4)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Systemic health effects	Dermal	12.1 mg/kg bw/d	
worker Systemic health effects Long term	Dermal	12.1 mg/kg bw/d	
worker Short term Systemic health effects	Inhalation	85 mg/m ³	
worker Short term Local health effects	Inhalation	85 mg/m ³	
worker Long term Systemic health effects	Inhalation	85 mg/m ³	
worker Long term Local health effects	Inhalation	85 mg/m ³	

Derived No Effect Level (DNEL)			
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)			
Type	Exposure route	Derived No Effect Level	Safety factor

SAFETY DATA SHEET

beko Hydro-Stop Sockelbeschichtung - pastös
Supersedes Date: 03-Nov-2022

Revision date 15-Mar-2023
Revision Number 2.01

		(DNEL)	
Consumer Long term Systemic health effects	Dermal	0.8 mg/kg	
Consumer Long term Systemic health effects	Oral	0.4 mg/kg	

Trimethoxyvinylsilane (2768-02-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m ³	
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d	
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d	

Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects Consumer	Oral	2.5 mg/kg bw/d	
Long term Systemic health effects Consumer	Inhalation	8.7 mg/m ³	
Long term Systemic health effects Consumer	Dermal	mg/kg bw/d	

Dioctyltin oxide (870-08-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	0.0005 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	0.025 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	0.0009 mg/m ³	

Ethyl silicate (78-10-4)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Dermal	8.4 mg/kg bw/d	

SAFETY DATA SHEET

beko Hydro-Stop Sockelbeschichtung - pastös
Supersedes Date: 03-Nov-2022

Revision date 15-Mar-2023
Revision Number 2.01

Consumer Long term Systemic health effects	Dermal	8.4 mg/kg bw/d	
Consumer Short term Systemic health effects	Inhalation	25 mg/m ³	
Consumer Short term Local health effects	Inhalation	25 mg/m ³	
Consumer Long term Systemic health effects	Inhalation	25 mg/m ³	
Consumer Long term Local health effects	Inhalation	25 mg/m ³	

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.018 mg/l
Marine water	0.0018 mg/l
Freshwater sediment	29 mg/kg
Marine sediment	2.9 mg/kg
Soil	5.9 mg/kg

Trimethoxyvinylsilane (2768-02-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.062 mg/l
Marine water	0.0062 mg/l
Freshwater - intermittent	0.62 mg/l
Freshwater sediment	0.05 mg/kg
Marine sediment	0.005 mg/kg
Soil	0.0075 mg/kg
Sewage treatment plant	25 mg/l

Diocetyl tin oxide (870-08-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater sediment	0.02798 mg/kg dry weight
Marine sediment	0.002798 mg/kg dry weight
Microorganisms in sewage treatment	100 mg/l

Ethyl silicate (78-10-4)	
--------------------------	--

SAFETY DATA SHEET

beko Hydro-Stop Sockelbeschichtung - pastös
Supersedes Date: 03-Nov-2022

Revision date 15-Mar-2023
Revision Number 2.01

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.192 mg/l
Marine water	0.0192 mg/l
Freshwater sediment	0.18 mg/kg dry weight
Marine sediment	0.018 mg/kg dry weight
Soil	0.05 mg/kg

8.2. Exposure controls

Engineering controls

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.

Hand protection

Wear suitable gloves. Recommended Use: Nitrile rubber. Butyl rubber. Glove thickness > 0.4 mm. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time for the mentioned glove material is in general greater than 480 min. Gloves must conform to standard EN 374

Skin and body protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better.

Recommended filter type:

Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Paste
Colour	Grey
Odour	Characteristic.
Odour threshold	No information available

Property	Values	Remarks • Method
Melting point / freezing point	No data available	
Initial boiling point and boiling range	No data available	
Flammability	Not applicable for liquids	
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	> 61 °C	CC (closed cup)
Autoignition temperature	No data available	
Decomposition temperature		None known
pH	.	Not applicable. Reacts with water.
pH (as aqueous solution)	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	27 - 35 Pa.s	Spindle Z3U @ 100 rpm @ 23 °C
Water solubility	Reacts with water. Product cures with moisture	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Vapour pressure	No data available	
Relative density	1.5	
Bulk Density	No data available	
Liquid Density	No data available	
Relative vapour density	No data available	
Particle characteristics		

SAFETY DATA SHEET

beko Hydro-Stop Sockelbeschichtung - pastös
Supersedes Date: 03-Nov-2022

Revision date 15-Mar-2023
Revision Number 2.01

Particle Size No information available
Particle Size Distribution No information available

9.2. Other information

Solid content (%) No information available
VOC content No data available

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.
Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Protect from moisture. Product cures with moisture.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.
Eye contact Based on available data, the classification criteria are not met.
Skin contact Based on available data, the classification criteria are not met.
Ingestion Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

beko Hydro-Stop Sockelbeschichtung - pastös
Supersedes Date: 03-Nov-2022

Revision date 15-Mar-2023
Revision Number 2.01

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	>5000 mg/kg
ATEmix (dermal)	13,578.10 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapour)	>20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	LD50 (Rattus) > 2000 mg/kg OECD 423	LD50 (Rattus) > 3 170 mg/kg OECD 402	=500 mg/m ³ (Rattus) 4 h
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg (Rattus) OECD 401	= 3540 mg/kg (Oryctolagus cuniculus)	LC50 (4hr) 16.8 mg/l (Rattus) OECD TG 403
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus) 4 h
N-(3-(trimethoxysilyl)propyl)ethylenediamine	LD50 = 2295 mg/kg (Rattus) EPA OPPTS 870.1100	LD50 > 2000 mg/kg (Oryctolagus cuniculus) EPA OPPTS 870.1200	1.49 - 2.44 mg/L (Rat) 4 h
Dioctyltin oxide	=2500 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus) OECD 402	-
Ethyl silicate	LD50 > 2500 mg/kg (Rattus) OECD 423	= 5878 mg/kg (Oryctolagus cuniculus) = 6300 µL/kg (Oryctolagus cuniculus)	= 10 mg/L (Rat male) 4 h > 16.8 mg/L (Rat female) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

SAFETY DATA SHEET

beko Hydro-Stop Sockelbeschichtung - pastös
Supersedes Date: 03-Nov-2022

Revision date 15-Mar-2023
Revision Number 2.01

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			Eye Damage

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye		24 hours	Non-irritant

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye			Non-irritant

Respiratory or skin sensitisation May produce an allergic reaction. OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. No classification is proposed, based on conclusive negative data.

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig		No sensitisation responses were observed

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation, Buehler test	Guinea pig	Dermal	sensitising

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	Not a skin sensitiser
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse	Dermal	Not a skin sensitiser

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Component Information

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 471: Bacterial Reverse Mutation Test	in vitro	Not mutagenic

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

beko Hydro-Stop Sockelbeschichtung - pastös
Supersedes Date: 03-Nov-2022

Revision date 15-Mar-2023
Revision Number 2.01

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Species	Results
OECD Test No. 414: Pre-natal Development Toxicity Study	Rat, Rabbit	reproductive toxicant

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Not Classifiable

STOT - single exposure

Based on available data, the classification criteria are not met.

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)
Diocetyl tin oxide (870-08-6)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Oral	5 mg/kg	28 days	0.3 - 0.5 mg/kg bw/d May cause damage to the following organs: Immune system

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)
Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413: Sub-chronic Inhalation Toxicity: 90-day Study	Rat	Inhalation vapour		90 days	0.058 NOAEL

Diocetyl tin oxide (870-08-6)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rat Rabbit			28 days	0.3 -0.5 mg/kg bw/d

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
---------------	---------------	------	-------------	-----------	----------	----------

SAFETY DATA SHEET

beko Hydro-Stop Sockelbeschichtung - pastös
Supersedes Date: 03-Nov-2022

Revision date 15-Mar-2023
Revision Number 2.01

	plants		microorganisms			(long-term)
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	EC50 72Hr 0.705 mg/l (Pseudokirchnerella subcapitata)	LC50 (96h) = 5.29 mg/l (Oryzias latipes)	-	LC50 48Hr 8.58 mg/l (Daphnia magna)		
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	-	LC50 (96H) =597 mg/L (Danio rerio)Semi-static	-	EC50 (48h) =81mg/L Daphnia magna Static		
Diocetyl tin oxide 870-08-6	EC50 (3hr) >1.000 mg/l (bacteria) (Activated Sludge, Respiration Inhibition Test)	LC50 (96hr) >0,09 mg/l (Brachydanio rerio (zebra)) (Acute Toxicity Test)	-	EC50 (48Hr) >0,21 mg/l (Daphnia magna (Daphnia magna)) (Daphnia sp. Acute Immobilisation Test)		
Ethyl silicate 78-10-4	EC 50 (72h) > 100 mg/L (Pseudokirchnerella subcapitata) OECD 201	LC50 (96h)> 245 mg/L (Danio rerio) EU Method C.1	-	-		

12.2. Persistence and degradability

Persistence and degradability No information available.

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Exposure time	Value	Results
OECD Test No. 303: Simulation Test - Aerobic Sewage Treatment -- A: Activated Sludge Units; B: Biofilms	28 days	Total organic carbon (TOC)	24 % Moderate

Trimethoxyvinylsilane (2768-02-7)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	BOD	51 % Not readily biodegradable

Diocetyl tin oxide (870-08-6)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	755 hours	biodegradation	Not readily biodegradable 2 %

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

SAFETY DATA SHEET

beko Hydro-Stop Sockelbeschichtung - pastös
Supercedes Date: 03-Nov-2022

Revision date 15-Mar-2023
Revision Number 2.01

Chemical name	Partition coefficient
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	0.35
Trimethoxyvinylsilane	1.1
N-(3-(trimethoxysilyl)propyl)ethylenediamine	-0.3
Dioctyltin oxide	6
Ethyl silicate	3.18

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	The substance is not PBT / vPvB
Trimethoxyvinylsilane	The substance is not PBT / vPvB
Titanium dioxide	The substance is not PBT / vPvB PBT assessment does not apply
N-(3-(trimethoxysilyl)propyl)ethylenediamine	The substance is not PBT / vPvB
Dioctyltin oxide	The substance is not PBT / vPvB
Ethyl silicate	The substance is not PBT / vPvB PBT assessment does not apply

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number Not regulated

14.2 Proper Shipping Name Not regulated

14.3 Transport hazard class(es) Not regulated

14.4 Packing group Not regulated

14.5 Environmental hazards Not applicable

14.6 Special precautions for user

Special Provisions None

SAFETY DATA SHEET

beko Hydro-Stop Sockelbeschichtung - pastös
Supersedes Date: 03-Nov-2022

Revision date 15-Mar-2023
Revision Number 2.01

IMDG

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special precautions for user	
Special Provisions	None
14.7 Maritime transport in bulk according to IMO instruments	
Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Diocetyl tin oxide	870-08-6	20.

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product contains substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals

Chemical name	European Export/Import Restrictions per (EC) 689/2008 - Annex Number
Diocetyl tin oxide	I.1

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

SAFETY DATA SHEET

beko Hydro-Stop Sockelbeschichtung - pastös
Supersedes Date: 03-Nov-2022

Revision date 15-Mar-2023
Revision Number 2.01

Persistent Organic Pollutants
Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H335 - May cause respiratory irritation
H361f - Suspected of damaging fertility
H400 - Very toxic to aquatic life
H411 - Toxic to aquatic life with long lasting effects

Notes relating to the identification, classification and labelling of substances

Note V: If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

Note W: It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung

Notes relating to the classification and labelling of mixtures

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

SAFETY DATA SHEET

beko Hydro-Stop Sockelbeschichtung - pastös
Supersedes Date: 03-Nov-2022

Revision date 15-Mar-2023
Revision Number 2.01

Revision date 15-Mar-2023

Indication of changes

Revision note SDS sections updated, 1, 11.

Training Advice No information available

Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet