

Adhesive Lubricant

High-Power

► Professional quality

Features

- High pressure resistant
- Extremely high adhesion
- Permanent lubrication
- Transparent colour
- Silicone-free
- Epoxy-free
- Displaces water
- Protects from corrosion
- Long-term impact
- Excellent penetration
- High yield
- Temperature resistant from -30° C to +240° C
- Resistant to acids and alkalis
- Water and saltwater resistant

Benefits of use

- Multi-purpose
- Optimal dosing
- Suitable for indoor and outdoor use
- Prevents cold welding on stainless steel

Areas of application

- Chains
- Gears
- Threads
- Construction machinery
- Lorry and car maintenance
- Drive chains (o-ring and x-ring compatible)
- Window fittings
- Hinges
- Wire cables



Adhesive Lubricant

Content 150 ml
Art.-No. 298 1 150EN

Content 500 ml
Art.-No. 298 1 500EN

Range of use

- ▶ Construction industry
- ▶ Automotive business
- ▶ Metal trade
- ▶ Industry

Directions for use

Cleans surfaces of rough impurities. **TecLine adhesive lubricant** comes at low viscosity from a can. Due to this feature the lubricant flows easily into impenetrable areas. High adhesive lubricating film after evaporation of solvent that resists high pressure, vibration and shocks.

Caution

- ▶ Shake before use.
- ▶ Not for use in precision engineering under any circumstances!
- ▶ Do not use in food areas.
- ▶ In the case of incorrect or improper application, any product warranty becomes void.
- ▶ For professional and industrial use only.
- ▶ Please observe safety data sheet!

Technical data

Basis	Mineral synthesis oil with additives			
Processable	from +5° C to max. +40° C			
Temperature	resistant from -30° C up to +240° C			
Colour	transparent yellow			
Smell	no smell			
Density	approx. 0,69 g/cm ³			
Viscosity	low viscosity, paste-like after evaporation of solvent			
Storage life	approx. 2 years			
Storage	dry, at room temperature			
Contents/packaging	Can 150 ml	12 pcs/box	1440 pcs/pallet	Art.-No. 298 1 150EN
	Can 500 ml	12 pcs/box	840 pcs/pallet	Art.-No. 298 1 500EN