

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.11.2017

Revision: 13.11.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· **Trade name:** beko Allbond Aktivatorspray 30 ml

UFI: 5990-U09W-300A-8A2Q

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· **Application of the substance / the mixture** Activating spray for CA-glue

· 1.3 Details of the supplier of the safety data sheet

· **Manufacturer/Supplier:**

beko GmbH

Rappenfeldstr. 5

DE-86653 Monheim

Tel. +49 (0) 9091 90898-0

· **Further information obtainable from:**

Produktsicherheit

Tel. +49 (0) 9091 90898-0

e-mail: info@beko-group.com

· **1.4 Emergency telephone number:** Poison Control Center Mainz - 24 hour – phone: +49 (0) 6131/19240

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· **Classification according to Regulation (EC) No 1272/2008**

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

· **Labelling according to Regulation (EC) No 1272/2008**

The labelling of an aspiration hazard (Asp. Tox. 1 H304) is not required for aerosols and containers with a sealed spray attachment (Regulation (EC) 1272/2008, Annex I, 1.3.3).

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02

GHS07

GHS09

· **Signal word** Danger

· **Hazard-determining components of labelling:**

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics.

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

Propan-2-ol

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.11.2017

Revision: 13.11.2017

Trade name: beko Allbond Aktivatorspray 30 ml

(Contd. of page 1)

- P271 Use only outdoors or in a well-ventilated area.
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
 P501 Dispose of contents / container as special waste.
- Additional information:**
 Without sufficient ventilation formation of explosive mixtures may be possible.
 Keep out of the reach of children
- 2.3 Other hazards**
- Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
 - **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description:

Mixture of substances listed below with nonhazardous compounds or compounds with no duty to declare.

Dangerous components:

EC number: 931-254-9 Reg.nr.: 01-2119484651-34	Hydrocarbons, C6, isoalkanes, <5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	25-50%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1, H220; Acute Tox. 1, H330; Press. Gas L, H280	10-25%
EC number: 927-510-4 Reg.nr.: 01-2119475515-33	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics. Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	≥15-≤25%
EC number: 926-605-8 Reg.nr.: 01-2119486291-36	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	2.5-10%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	Propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	2.5-10%
CAS: 110-82-7 EINECS: 203-806-2	cyclohexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336	≥0.25-≤2.5%
CAS: 110-54-3 EINECS: 203-777-6	n-hexane Flam. Liq. 2, H225; Repr. 2, H361f; STOT RE 2, H373; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	≥0.25-≤2.5%
CAS: 99-97-8 EINECS: 202-805-4	N,N-dimethyl-p-toluidine Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; STOT RE 2, H373; Aquatic Chronic 3, H412	≥0.1-≤1%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Take affected persons out into the fresh air.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.11.2017

Revision: 13.11.2017

Trade name: beko Allbond Aktivatorspray 30 ml

(Contd. of page 2)

- Do not leave affected persons unattended.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
Intensive inhalation may cause:
Dizziness
Dizziness
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** Risk of bursting in case of fire heat
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear fully protective suit.
- **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Avoid contact with skin / eyes and inhalation.
Keep sources of ignition (flames, sparks, etc.) away. Do not use engines near by (potential source of ignition)
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Open and handle receptacle with care.
Avoid inhalation and contact with the skin and the eyes.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray onto a naked flame or any incandescent material.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Store away from oxidising agents.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.11.2017

Revision: 13.11.2017

Trade name: beko Allbond Aktivatorspray 30 ml

(Contd. of page 3)

- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Recommended storage temperature:** 15 - 35°C, max. 50°C
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· Ingredients with limit values that require monitoring at the workplace:

Hydrocarbons, C6, isoalkanes, <5% n-hexane

RCP-TWA (Great Britain) Long-term value: 1400 mg/m³

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics.

RCP-TWA (Great Britain) Long-term value: 1400 mg/m³

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

RCP-TWA (Great Britain) Long-term value: 1400 mg/m³

67-63-0 Propan-2-ol

WEL (Great Britain) Short-term value: 1250 mg/m³, 500 ppm
Long-term value: 999 mg/m³, 400 ppm

110-82-7 cyclohexane

WEL (Great Britain) Short-term value: 1050 mg/m³, 300 ppm
Long-term value: 350 mg/m³, 100 ppmIOELV (EU) Long-term value: 700 mg/m³, 200 ppm

110-54-3 n-hexane

WEL (Great Britain) Long-term value: 72 mg/m³, 20 ppmIOELV (EU) Long-term value: 72 mg/m³, 20 ppm

· DNELs

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Oral	DNEL Endverbraucher/ Consumers /Consommateur	1,301 mg/kg BW/ day (.)
Dermal	DNEL - Endverbraucher/ Consumers /Consommateur	1,377 mg/kg BW /day (.)
	DNEL Arbeiter / Workers/ Travailleur	13,964 mg/kg BW /day (.)
Inhalative	DNEL Endverbraucher/ Consumers /Consommateur	1,137 mg /m ³ (.)
	DNEL Arbeiter / Workers/ Travailleur	5,306 mg /m ³ (.)

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics.

Oral	DNEL Endverbraucher/ Consumers /Consommateur	149 mg/kg BW/ day (hum)
Dermal	DNEL - Endverbraucher/ Consumers /Consommateur	149 mg/kg BW /day (.)
	DNEL Arbeiter / Workers/ Travailleur	300 mg/kg BW /day (.)
Inhalative	DNEL Endverbraucher/ Consumers /Consommateur	477 mg /m ³ (.)
	DNEL Arbeiter / Workers/ Travailleur	2,085 mg /m ³ (.)

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

Oral	DNEL Endverbraucher/ Consumers /Consommateur	1,301 mg/kg BW/ day (.)
Dermal	DNEL - Endverbraucher/ Consumers /Consommateur	1,377 mg/kg BW /day (.)
	DNEL Arbeiter / Workers/ Travailleur	13,964 mg/kg BW /day (.)
Inhalative	DNEL Endverbraucher/ Consumers /Consommateur	1,131 mg /m ³ (.)
	DNEL Arbeiter / Workers/ Travailleur	5,306 mg /m ³ (.)

67-63-0 Propan-2-ol

Oral DNEL Endverbraucher/ Consumers /Consommateur 26 mg/kg BW/ day (.)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.11.2017

Revision: 13.11.2017

Trade name: beko Allbond Aktivatorspray 30 ml

(Contd. of page 4)

Dermal	DNEL - Endverbraucher/ Consumers /Consommateur	319 mg/kg BW /day (.)
	DNEL Arbeiter / Workers/ Travailleur	888 mg/kg BW /day (.)
Inhalative	DNEL Endverbraucher/ Consumers /Consommateur	89 mg /m3 (.)
	DNEL Arbeiter / Workers/ Travailleur	500 mg /m3 (.)

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Aerosol

Colour: Colourless

· **Odour:** Amine-like

· **pH-value:** Not determined.

· **Change in condition**

Initial boiling point and boiling range: -42°C

value concerns to propellant

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.11.2017

Revision: 13.11.2017

Trade name: beko Allbond Aktivatorspray 30 ml

(Contd. of page 5)

· Flash point:	-97°C concerns to propellant
· Ignition temperature:	250°C
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Risk of bursting at temperatures > 50°C. Damage of the container may lead to the formation of explosive mixtures of gas/vapors with air.
· Explosion limits:	
Lower:	0.8 Vol %
Upper:	10.9 Vol %
Pressure (20°C)	2.5 - 5.0 bar
· Density at 20°C:	0.667 g/cm ³
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Solvent content:	
Organic solvents:	ca. 74.2 %
VOC (EC)	100.00 % = 667 g/l
· 9.2 Other information	No further relevant information available.
· Additional information	Vapors are heavier than air.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** Risk of bursting at temperatures >50°C.
- **10.3 Possibility of hazardous reactions**
By use or incidental release the formation of explosive vapor/air mixtures is possible.
- **10.4 Conditions to avoid** Temperatures >50°C
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** In case of fire the formation of toxic gases is possible.
- **Additional information:** Stable for a storage time of min. 24 months

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

74-98-6 propane

Inhalative	LC50/4 h	>20 mg/l (rat)
------------	----------	----------------

67-63-0 Propan-2-ol

Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)

110-82-7 cyclohexane

Oral	LD50	12,705 mg/kg (rat)
------	------	--------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation** low irritant

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.11.2017

Revision: 13.11.2017

Trade name: beko Allbond Aktivatorspray 30 ml

(Contd. of page 6)

- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**
May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
empty cans: material recycling
filled cans: remove in accordance with local regulations

· **European waste catalogue**

16 00 00	WASTES NOT OTHERWISE SPECIFIED IN THE LIST
16 05 00	gases in pressure containers and discarded chemicals
16 05 04*	gases in pressure containers (including halons) containing hazardous substances

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR** 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
- **IMDG** AEROSOLS (Naphtha (petroleum), hydrotreated light, CYCLOHEXANE), MARINE POLLUTANT

(Contd. on page 8)




Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.11.2017

Revision: 13.11.2017

Trade name: beko Allbond Aktivatorspray 30 ml

(Contd. of page 7)

· IATA	<i>AEROSOLS, flammable</i>
· 14.3 Transport hazard class(es)	
· ADR	
	
· Class	2 5F Gases.
· Label	2.1
· IMDG	
	
· Class	2.1
· Label	2.1
· IATA	
	
· Class	2.1
· Label	2.1
· 14.4 Packing group	
· ADR, IMDG, IATA	<i>Void</i>
· 14.5 Environmental hazards:	<i>Product contains environmentally hazardous substances: cyclohexane, Naphtha (petroleum), hydrotreated light</i>
· Marine pollutant:	<i>Yes</i>
· Special marking (ADR):	<i>Symbol (fish and tree)</i>
· 14.6 Special precautions for user	<i>Warning: Gases.</i>
· Danger code (Kemler):	<i>-</i>
· EMS Number:	<i>F-D,S-U</i>
· Stowage Code	<i>SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.</i>
· Segregation Code	<i>SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.</i>
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	<i>Not applicable.</i>
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	<i>IL</i>
· Excepted quantities (EQ)	<i>Code: E0 Not permitted as Excepted Quantity</i>

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.11.2017

Revision: 13.11.2017

Trade name: beko Allbond Aktivatorspray 30 ml

(Contd. of page 8)

· Transport category	2
· Tunnel restriction code	D
· Remarks:	Transportation as "LIMITED QUANTITIES" according 3.4 ADR is possible. Sole marking: Sign for "Limited Quantities" (rhombus with two black edges) Entry in the transportation document: Transportation according chapter 3.4 ADR Tunnel category "E" in case of a load of 8000 kg (rgross weight) or more.
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**
P3a FLAMMABLE AEROSOLS
E2 Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations:**
- **Information about limitation of use:**
Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.

Class	Share in %
I	2.2
NK	49.8

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H301 Toxic if swallowed.
H304 May be fatal if swallowed and enters airways.
H311 Toxic in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H331 Toxic if inhaled.
H336 May cause drowsiness or dizziness.

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.11.2017

Revision: 13.11.2017

Trade name: beko Allbond Aktivatorspray 30 ml

(Contd. of page 9)

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas L: Gases under pressure – Liquefied gas

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 1: Acute toxicity – Category 1

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the previous version altered.**

GB