Printing date 10.11.2023

Version number 1

Revision: 10.11.2023

#### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### 1.1 Product identifier

• Trade name: beko Montageschaum B3

- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture One-component polyurethane foam hand held

#### 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: BEKO GMBH RAPPENFELDSTRASSE 5 DE-86653 MONHEIM
- Further information obtainable from: Tel: + 49 9091 90898-0 Fax:+ 49 9091 9089829

## • **1.4 Emergency telephone number:** Poison Control Center Mainz - 24 hour emergency service - phone: +49 (0) 6131/19240

### **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture None

Classification according to Regulation (EC) No 1272/2008
 None

	NONE		
	Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
	Acute Tox. 4	H332	Harmful if inhaled.
	Skin Irrit. 2	H315	Causes skin irritation.
	Eye Irrit. 2	H319	Causes serious eye irritation.
	Resp. Sens. 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
	Skin Sens. 1	H317	May cause an allergic skin reaction.
	Carc. 2	H351	Suspected of causing cancer.
	Lact.	H362	May cause harm to breast-fed children.
	STOT SE 3	H335	May cause respiratory irritation.
	STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.
_	Aquatic Chronic 4	H413	May cause long lasting harmful effects to aquatic life.
_			

#### <sup>•</sup> 2.2 Label elements

#### <sup>•</sup> Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



(Contd. on page 2)

EU

Revision: 10.11.2023

#### Printing date 10.11.2023 Version number 1 Trade name: beko Montageschaum B3 (Contd. of page 1) · Hazard-determining components of labelling: diphenylmethanediisocyanate, isomeres and homologues alkanes, C14-17, chloro Hazard statements H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. H332 Harmful if inhaled. Causes skin irritation. H315 H319 Causes serious eye irritation. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317 May cause an allergic skin reaction. H351 Suspected of causing cancer. H362 May cause harm to breast-fed children. H335 May cause respiratory irritation. H373 May cause damage to organs through prolonged or repeated exposure. H413 May cause long lasting harmful effects to aquatic life. · Precautionary statements P102 Keep out of reach of children. P201 Obtain special instructions before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. P210 No smokina. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P260 Do not breathe vapours/spray. Wear protective gloves/protective clothing/eye protection. P280 P284 In case of inadequate ventilation wear respiratory protection (a protective mask with an appropriate gas filter - i.e. type A1 according to standard EN 14387). P302+P352 IF ON SKIN: Wash with plenty of water/soap. IF INHALED: Remove person to fresh air and keep comfortable for breathing. P304+P340 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 IF exposed or concerned: Get medical advice/attention. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of container to in accordance with local/regional/national/international regulation. · Additional information: - Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used. As from 24 August 2023 adequate training is required before industrial or professional use. EUH204 Contains isocyanates. May produce an allergic reaction. <sup>•</sup> 2.3 Other hazards · Results of PBT and vPvB assessment Not applicable. · PBT: CAS: 85535-85-9 alkanes, C14-17, chloro · vPvB: CAS: 85535-85-9 alkanes, C14-17, chloro

(Contd. on page 3)

ΕU

Printing date 10.11.2023

Version number 1

Revision: 10.11.2023

#### Trade name: beko Montageschaum B3

(Contd. of page 2)

Dangerous components:	cription: Mixture of substances listed below with nonhazardous additions. gerous components:				
CAS: 9016-87-9	diphenylmethanediisocyanate,isomeres and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Skin Irrit. 2; H315: $C \ge 5$ % Eye Irrit. 2; H319: $C \ge 5$ % Resp. Sens. 1; H334: $C \ge 0.1$ % STOT SE 3; H335: $C \ge 5$ %	25-30%			
CAS: 85535-85-9 EINECS: 287-477-0 Index number: 602-095-00-X	alkanes, C14-17, chloro Acute Tox. 2, H330; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Lact., H362, EUH066 PBT; vPvB	10-20%			
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-01-8	isobutane � Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-15%			
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8	dimethyl ether	1-10%			
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5	propane	1-10%			

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After swallowing: If symptoms persist consult doctor.

• **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

(Contd. on page 4)

EU •

Printing date 10.11.2023

Version number 1

Revision: 10.11.2023

#### Trade name: beko Montageschaum B3

(Contd. of page 3)

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

• Suitable extinguishing agents:

Foam

Use fire extinguishing methods suitable to surrounding conditions.

• For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released: Nitrogen oxides (NOx) Carbon monoxide (CO) Hydrogen cyanide (HCN)

- 5.3 Advice for firefighters
- Protective equipment: Mouth respiratory protective device.
- Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

## **SECTION 6: Accidental release measures**

<sup>•</sup> **6.1 Personal precautions, protective equipment and emergency procedures** Keep away from ignition sources.

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:
 Inform respective authorities in case of seepage into water course or sewage system.
 Do not allow to enter sewers/ surface or ground water.

**6.3 Methods and material for containment and cleaning up:** Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

<sup>•</sup>7.1 Precautions for safe handling

Ensure that suitable extractors are available on processing machines Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.

- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- <sup>•</sup> 7.2 Conditions for safe storage, including any incompatibilities <sup>•</sup> Storage:
- **Requirements to be met by storerooms and receptacles:** Store in a cool location. Store only in the original receptacle.

(Contd. on page 5)

EU

Version number 1

Revision: 10.11.2023

#### Trade name: beko Montageschaum B3

(Contd. of page 4) Observe official regulations on storing packagings with pressurised containers. • Information about storage in one common storage facility: Store away from oxidising agents. • Further information about storage conditions: Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting. Protect from humidity and water.

Keep container tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· Storage class: 2B

Printing date 10.11.2023

<sup>•</sup> 7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

#### <sup>•</sup> 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

#### CAS: 115-10-6 dimethyl ether

IOELV Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm

• Additional information: The lists valid during the making were used as basis.

#### <sup>•</sup> 8.2 Exposure controls

- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

## • Hand protection



Protective gloves

Protective gloves according to EN 374.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

- EU ·

Printing date 10.11.2023

Version number 1

Revision: 10.11.2023

(Contd. of page 5)

## Trade name: beko Montageschaum B3

· Eye/face protection



Tightly sealed goggles

Wear airtight protective goggles EN 166 • **Body protection:** Protective work clothing EN 13688

SECTION 9: Physical and chemical pro	perties
9.1 Information on basic physical and o	chemical properties
· General Information	
Physical state	Aerosol
· Colour:	According to product specification
· Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling	
range	Not applicable, as aerosol.
· Flammability	Not applicable.
Lower and upper explosion limit	•••
· Lower:	3.0 Vol %
· Upper:	18.6 Vol %
Flash point:	Not applicable, as aerosol.
Auto-ignition temperature:	199 °C
Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Fully miscible.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
Density and/or relative density	
Density:	Not determined.
· Relative density	Not determined.
· Vapour density	Not determined.
9.2 Other information	
· Appearance: · Form:	Aerosol
	Aerosor
<ul> <li>Important information on protection of health and environment, and on safety.</li> </ul>	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Not determined.
· Solvent content:	
· VOC (EC)	25.70 %
	(Contd. on page 7)

EU -

Printing date 10.11.2023

Version number 1

Revision: 10.11.2023

#### Trade name: beko Montageschaum B3

	(Contd. of page
Change in condition	
Evaporation rate	Not applicable.
Information with regard to physical hazard	
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised
	container: May burst if heated.
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

### **SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- <sup>•</sup> 10.2 Chemical stability
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- 10.6 Hazardous decomposition products:
- Hydrogen cyanide (prussic acid) Carbon monoxide Nitrogen oxides (NOx)

## **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Harmful if inhaled.

#### · LD/LC50 values relevant for classification:

#### CAS: 115-10-6 dimethyl ether

Inhalative LC50/4 h 308 mg/l (rat)

Skin corrosion/irritation Causes skin irritation.

· Serious eye damage/irritation Causes serious eye irritation.

(Contd. on page 8)

EU

Printing date 10.11.2023

Version number 1

Revision: 10.11.2023

#### Trade name: beko Montageschaum B3

#### · Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Suspected of causing cancer.
- Reproductive toxicity May cause harm to breast-fed children.
- **STOT-single exposure** May cause respiratory irritation.
- STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.
- Aspiration hazard Based on available data, the classification criteria are not met.

#### 11.2 Information on other hazards

#### · Endocrine disrupting properties

None of the ingredients is listed.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- <sup>•</sup> **12.2 Persistence and degradability** No further relevant information available.
- <sup>•</sup> **12.3 Bioaccumulative potential** No further relevant information available.
- <sup>•</sup> **12.4 Mobility in soil** No further relevant information available.

#### <sup>•</sup> **12.5 Results of PBT and vPvB assessment** Not applicable.

· PBT:

CAS: 85535-85-9 alkanes, C14-17, chloro

#### · vPvB:

CAS: 85535-85-9 alkanes, C14-17, chloro

#### 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue					
08 05 01* waste isocyanates					
16 05 04* gases in pressure containers (including halons) containing hazardous substances					
15 01 10* packaging containing residues of or contaminated by hazardous substances					

(Contd. on page 9)

(Contd. of page 7)

Version number 1

Revision: 10.11.2023

(Contd. of page 8)

#### Trade name: beko Montageschaum B3

· Uncleaned packaging:

Printing date 10.11.2023

• **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information		
<sup>·</sup> 14.1 UN number or ID number <sup>·</sup> ADR, IMDG, IATA	1950	
<ul> <li>14.2 UN proper shipping name</li> <li>ADR</li> <li>IMDG, IATA</li> </ul>	1950 AEROSOLS AEROSOLI	
<sup>•</sup> 14.3 Transport hazard class(es)		
· ADR · Class · Label	2 5F Gases. 2.1	
<ul> <li>IMDG, IATA</li> <li>Class</li> <li>Label</li> </ul>	2.1 Gases. 2.1	
<ul> <li>14.4 Packing group</li> <li>ADR, IMDG, IATA</li> </ul>	Void	
• 14.5 Environmental hazards: • Marine pollutant:	No	
14.6 Special precautions for use EMS Number:	er Warning: Gases. F-D,S-U	
14.7 Maritime transport in bulk a	according to IMO instruments	
· Transport/Additional information:		
<ul> <li>ADR</li> <li>Limited quantities (LQ)</li> </ul>	1L	
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1	

## **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Directive 2012/18/EU

• Named dangerous substances - ANNEX I None of the ingredients is listed.

• Seveso category P3a FLAMMABLE AEROSOLS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

(Contd. on page 10)

EU

Version number 1

Revision: 10.11.2023

Trade name: beko Montageschaum B3

Printing date 10.11.2023

(Contd. of page 9) • Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t • DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in
electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

 Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

 Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

· Other regulations, limitations and prohibitive regulations

• Substances of very high concern (SVHC) according to REACH, Article 57

CAS: 85535-85-9 alkanes, C14-17, chloro

\* 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H220 Extremely flammable gas.
- H280 Contains gas under pressure; may explode if heated.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H362 May cause harm to breast-fed children.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH204 Contains isocyanates. May produce an allergic reaction.

Date of previous version: 10.11.2023

#### · Abbreviations and acronyms:

Flam. Gas 1A: Flammable gases – Category 1A Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure – Compressed gas Acute Tox. 2: Acute toxicity – Category 2 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Printing date 10.11.2023

Version number 1

Revision: 10.11.2023

## Trade name: beko Montageschaum B3

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Resp. Sens. 1: Respiratory sensitisation – Category 1 Skin Sens. 1: Skin sensitisation – Category 1 Carc. 2: Carcinogenicity – Category 2 Lact.: Reproductive toxicity – effects on or via lactation STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1	(Contd. of page 10)
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4	