

SPEED-EX

The paint stripper

▶ Professional quality

Features

- ▶ Strips paint, removes and dissolves
- ▶ Highly effective after only 10 minutes
- ▶ Gentle to the substrates - powerful in effect
- ▶ Gel-form consistency
- ▶ Does not affect health or act as an irritant
- ▶ Contains no methylene chloride, N-methylpyrrolidone, biocides and preservatives
- ▶ Acid and alkali free

Benefits of use

- ▶ Easy handling
- ▶ Quick acting time
- ▶ Ready to paint
- ▶ Good stability on the surface
- ▶ Low odour formation
- ▶ Strong depth effect

Areas of application

- ▶ For quick and thorough removal of old paints and varnishes such as, for example, oil paints, alkyd and synthetic resin paints, acrylic and emulsion paints as well as 2-component systems, polyurethane materials, fillers and adhesives. Suitable for mineral substrates, metal, glass and wood.



SPEED-EX

The paint stripper

Content 750 ml
Art.-No. 299 60 0750EN

Other
chemical
products

Range of use

- ▶ Motor vehicle trade
- ▶ Metal construction
- ▶ Paint shops
- ▶ Painting and decorating
- ▶ Building trade
- ▶ Wood trade

Directions for use

Remove loose paint as much as possible. Open container carefully. Tin can be under light pressure. Apply a thick, even layer of **beko SPEED-EX** with a brush (flat or round). Do not use synthetic brushes. **beko SPEED-EX** leave to act for 10 to 15 minutes and then remove the old paint with a scraper or spatula. Thick layers and some (two component) paints may require additional treatment. After use, clean the surface with **beko Allclean** or pure water and then allow to dry completely before applying a coating.

Caution

- ▶ **beko SPEED-EX** can attack plastics such as PVC, polystyrene, etc.
- ▶ Perform compatibility test on the surface.
- ▶ Do not use in the immediate vicinity of fire, hot surfaces or welding work.
- ▶ In the case of incorrect or improper application, any product warranty becomes void.
- ▶ For professional and industrial use only.
- ▶ Please observe safety data sheet!

Technical data

Basis	special solvent mixture and paraffin wax			
Directions for use	from +5° C to +25° C			
Yield	300 to 500 g/m ²			
Time taken to act	10 to 15 Min.			
Colour	white/transparent			
Smell	slightly like ether			
Density	approx. 0.987 g/cm ³			
Viscosity	gel-form			
Storage life	at least 12 months			
Storage	at +5° C to +25° C, in dry, well-ventilated areas, no direct sunlight			
Contents/ packaging	Can 750 ml	6 pcs/box	660 pcs/pallet	Art.-No. 299 60 0750EN